arXiv:1110.4507v1 [math.NA] 20 Oct 2011

Approximation of pressure perturbations by FEM

Cătălin Liviu Bichir [1], Adelina Georgescu [2],
1 Research and Design Institute for Shipbuilding - ICEPRONAV
Galaţi, Romania,
2 University of Piteşti, Romania

October 21, 2011

Abstract

In the mathematical problem of linear hydrodynamic stability for shear flows against Tollmien-Schlichting perturbations, the continuity equation for the perturbation of the velocity is replaced by a Poisson equation for the pressure perturbation. The resulting eigenvalue problem, an alternative form for the two - point eigenvalue problem for the Orr - Sommerfeld equation, is formulated in a variational form and this one is approximated by finite element method (FEM). Possible applications to concrete cases are revealed.

Key words: linear hydrodynamic stability, pressure perturbation, Poisson equation, finite element method, eigenvalue problem.
2000 AMS subject classifications: 76E05 35J05 65L60 76M10 65F15.

1 The classical model and the model based on a Poisson equation for the pressure perturbation

The mathematical problem of linear hydrodynamic stability is [1]

$$\frac{\partial \mathbf{u}'}{\partial t} + (\mathbf{U} \cdot \mathbf{grad})\mathbf{u}' + (\mathbf{u}' \cdot \mathbf{grad})\mathbf{U} = \tag{1a}$$

$$= -\mathbf{grad}\ p' + Re^{-1} \triangle \mathbf{u}',\ (t, \mathbf{x}) \in \mathbb{R}_+ \times \Omega,$$

$$div\ \mathbf{u}' = 0,\ (t, \mathbf{x}) \in \mathbb{R}_+ \times \Omega, \tag{1b}$$

$$\mathbf{u}'(t, \mathbf{x}) = 0,\ t \in \mathbb{R}_+,\ \mathbf{x} \in \partial\Omega, \tag{1c}$$

$$\mathbf{u}'(0, \mathbf{x}) = \mathbf{u}'_0(\mathbf{x}),\ \mathbf{x} \in \Omega, \tag{1d}$$

and its solution is the perturbation $(\mathbf{u}', p')$, for $t > 0$. Here all variables are non dimensional, $(\mathbf{U}, P)$ is the basic motion in the domain $\Omega \subseteq \mathbb{R}^n$, $n = 2$ or 3, $Re = U_\infty L/\nu$ is the Reynolds number, L is a length scale, U_∞ is a velocity scale, ν is the coefficient of kinematic viscosity.

Applying the divergence operator to (1a) and using the divergence-free condition on $\mathbf{u}'$, we obtain

$$\begin{gathered}\triangle p' = -div \cdot ((\mathbf{U} \cdot \mathbf{grad})\mathbf{u}') - div \cdot ((\mathbf{u}' \cdot \mathbf{grad})\mathbf{U}),\\ (t, \mathbf{x}) \in \mathbb{R}_+ \times \Omega,\end{gathered} \tag{2}$$

and projecting (1a) on $\mathbf{n}_*$, we have

$$\begin{gathered}\mathbf{n}_*(\mathbf{x}) \cdot \mathbf{grad}\, p'(t, \mathbf{x}) = \mathbf{n}_*(\mathbf{x}) \cdot \mathbf{F}(Re, \mathbf{U}(\mathbf{x}), \mathbf{u}'(t, \mathbf{x})),\\ t \in \mathbb{R}_+,\ \mathbf{x} \in \partial\Omega,\end{gathered} \tag{3}$$

where $\mathbf{n}_*$ is the unit outward normal to $\partial\Omega$ and $\mathbf{F}(Re, \mathbf{U}, \mathbf{u}') = Re^{-1}\triangle\mathbf{u}' - (\mathbf{U} \cdot \mathbf{grad})\mathbf{u}' - (\mathbf{u}' \cdot \mathbf{grad})\mathbf{U}$. Another form of the right hand - side of the Poisson equation for p' can be obtained by using the divergence-free condition on $\mathbf{U}$.

Thus the mathematical problem of the linear hydrodynamic stability becomes (1a), (2), (1c), (3), (1d). Of course, it is assumed that equation (1a) can be continued on the $\partial\Omega$.

2 An alternative approximation of the two - point eigenvalue problem for Orr - Sommerfeld equation

Let $\Omega = \{\mathbf{x} = (x, y, z) \in \mathbb{R}^3 | -\infty < x, z < \infty, 0 < y < a\}$ $(a \geq 1)$ and assume that the basic flow is of the form $\mathbf{U}(x, y, z) = (U(y), 0, 0)$. Let us choose Tollmien-Schlichting waves - like perturbations $\mathbf{u}'(t, x, y, z) = \mathbf{u}'_0(y) exp[i\alpha(x - ct)]$, $\mathbf{u}'_0(y) = (u(y), v(y), 0)$, $\mathbf{u}'(t, x, y, z) = (u'(t, x, y), v'(t, x, y), 0)$, $p'(t, x, y, z) = p(y) exp[i\alpha(x - ct)]$, where $i = \sqrt{-1}$, α is the streamwise wave number, $c = c_r + ic_i$, c_r is the wave speed and c_i is the amplification rate.

In this case, model (1) leads to the classical two - point eigenvalue problem for Orr - Sommerfeld equation in (c, φ), where φ is the nonexponential factor of the stream function, while (1a), (2), (1c), (3), (1d) becomes the two - point eigenvalue problem in (c, u, v, p)

$$-\alpha Re^{-1} iu + (\alpha Re)^{-1} iu'' + Uu - \alpha^{-1} iU'v + p = cu,\ y \in (0, a), \tag{4a}$$

$$-\alpha Re^{-1} iv + (\alpha Re)^{-1} iv'' + Uv - \alpha^{-1} ip' = cv,\ y \in (0, a), \tag{4b}$$

$$-\alpha^2 p + p'' = -2\alpha i U' v,\ y \in (0, a), \tag{4c}$$

$$u(y) = 0 \ \text{ for } y = 0, y = a, \tag{4d}$$

$$v(y) = 0 \ \text{ for } y = 0, y = a, \tag{4e}$$

$$p'(y) = Re^{-1} v''(y) \ \text{ for } y = 0, y = a. \tag{4f}$$

where the prime stands for the differentiation with respect to y, c is an eigenvalue and (u, v, p) is an eigenvector.

Let $L^2(0,a)$ be the Hilbert space of all measurable complex-valued functions u, defined on $(0,a)$, for which $\int\limits_0^a |u(x)|^2 dx < \infty$ and the inner product is $(u,v) = \int\limits_0^a u\overline{v}dy$. Denote Du the generalized derivative and consider the spaces $H_0^1(0,a) = \{u \in L^2(0,a) | Du \in L^2(0,a), u(0) = u(a) = 0\}$, $L_0^2(0,a) = \{p \in L^2(0,a) \mid \int\limits_0^a p(x)\ dx = 0\}$.

Multiply (4a), (4b) and (4c) by arbitrary test functions $\overline{f}_1$, $\overline{f}_2$ and $\overline{g}$ respectively, integrate over $(0,a)$, apply partial integration if necessary and take into account the two point conditions (4d) - (4f) to obtain the following weak formulation of problem (4) in $(c,u,v,p) \in \mathbb{C} \times {H_0^1(0,a)}^2 \times L_0^2(0,a)$

$$\begin{aligned} &-\alpha Re^{-1} i \int_0^a u\overline{f}_1 dy - (\alpha Re)^{-1} i \int_0^a u'\overline{f}_1{}' dy + \int_0^a U u \overline{f}_1 dy - \\ &-\alpha^{-1} i \int_0^a U' v \overline{f}_1 dy + \int_0^a p\overline{f}_1 dy = c \cdot \int_0^a u \overline{f}_1 dy, \forall\ f_1 \in H_0^1(0,a), \end{aligned} \tag{5}$$

$$\begin{aligned} &-\alpha Re^{-1} i \int_0^a v\overline{f}_2 dy - (\alpha Re)^{-1} i \int_0^a v'\overline{f}_2{}' dy + \int_0^a U v \overline{f}_2 dy \\ &+\alpha^{-1} i \int_0^a p \overline{f}_2{}' dy = c \cdot \int_0^a v \overline{f}_2 dy, \forall\ f_2 \in H_0^1(0,a), \end{aligned} \tag{6}$$

$$\begin{aligned} &-\alpha^2 \int_0^a p\overline{g} dy - \int_0^a p'\overline{g}\,' dy = -Re^{-1} v''(a)\overline{g}(a) \\ &+ Re^{-1} v''(0)\overline{g}(0) - 2\alpha i \int_0^a U' v \overline{g} dy, \forall\ g \in L_0^2(0,a). \end{aligned} \tag{7}$$

3 Approximation of problem (5) - (7) by FEM

In order to perform this approximation, let us divide the interval $[0,a]$ in $N+1$ subintervals $K = K_j = [y_j, y_{j+1}]$, $0 \le j \le N$, where $0 = y_0 < y_1 < \ldots < y_{N+1} = a$. The sets K represent a triangulation $\mathcal{T}_h$ of $[0,a]$.

The approximate basic shear flow $\mathbf{U}_h(x,y,z) = (U_h(y),0,0)$ is defined by $U_h(y) = U(y)$, $y \in [0,a]$. The approximate amplitudes $u_h(y)$, $v_h(y)$ and $p_h(y)$ correspond to the exact ones, $u(y)$, $v(y)$ and $p(y)$, respectively.

Introduce the spaces $V_h = \{v : [0,a] \to \mathbb{C} \mid v \in C[0,a]$, v is on K_j an one - dimensional polynomial, having complex coefficients, of degree 2, $0 \le j \le N, v(0) = v(a) = 0\}$ and $M_h = \{v : [0,a] \to \mathbb{C} \mid v \in C[0,a]$, v is on K_j an one - dimensional polynomial, having complex coefficients, of degree 1, $0 \le j \le N\}$.

Correspondingly, variational problem (5) - (7) is approximated by the following problem in $(c_h, u_h, v_h, p_h) \in \mathbb{C} \times V_h^2 \times M_h$,

$$\begin{aligned} & -\alpha Re^{-1} i \int\limits_0^a u_h \overline{f}_1 dy - (\alpha Re)^{-1} i \int\limits_0^a u_h' \overline{f}_1{}' dy + \int\limits_0^a U u_h \overline{f}_1 dy - \\ & -\alpha^{-1} i \int\limits_0^a U' v_h \overline{f}_1 dy + \int\limits_0^a p_h \overline{f}_1 dy = c_h \cdot \int\limits_0^a u_h \overline{f}_1 dy, \forall\ f_1 \in V_h, \end{aligned} \tag{8}$$

$$\begin{aligned} & -\alpha Re^{-1} i \int\limits_0^a v_h \overline{f}_2 dy - (\alpha Re)^{-1} i \int\limits_0^a v_h' \overline{f}_2{}' dy + \int\limits_0^a U v_h \overline{f}_2 dy \\ & +\alpha^{-1} i \int\limits_0^a p_h \overline{f}_2{}' dy = c_h \cdot \int\limits_0^a v_h \overline{f}_2 dy, \forall\ f_2 \in V_h, \end{aligned} \tag{9}$$

$$\begin{aligned} & -\alpha^2 \int\limits_0^a p_h \overline{g} dy - \int\limits_0^a p_h' \overline{g}\,' dy = -Re^{-1} v_h''(a) \overline{g}(a) \\ & + Re^{-1} v_h''(0) \overline{g}(0) - 2\alpha i \int\limits_0^a U' v_h \overline{g} dy, \forall\ g \in M_h. \end{aligned} \tag{10}$$

In order to obtain u_h, v_h, we use a basis of real functions of V_h. Let $J = J_K = \{1, 2, 3\}$ be the local numeration for the nodes of K, where $1, 3$ correspond to y_j, y_{j+1} respectively and 2 corresponds to a node between y_j and y_{j+1}. Let $\{\phi_n, n \in J\}$ be the local quadratic basis of functions on K corresponding to the local nodes. Let $J_* = \{1, \ldots, 2N+1\}$ be the global numeration for the nodes of $[0,a]$, where the nodes corresponding to y_0 and y_{N+1} are not taken into account, and let L_1 be a matrix whose elements are the elements of J_*. Its rows are indexed by the elements $K \in \mathcal{T}_h$ and its columns, by the local numeration $n \in J$. We take the value 0 at the locations of L_1 which we do not consider in the computations, i.e. the locations where $K = K_0$, $n = 1$ and $K = K_N$, $n = 3$. Write $n_* = L_1(K, n)$ or, simply, n_* for the element n_* of L_1 which depends on K and n. Let $\{(\Phi_{n_*}, 0), (0, \Phi_{n_*}); n_* \in J_*\}$ be a basis of functions of V_h^2. If n_* corresponds to y_j, then Φ_{n_*} is a real quadratic function on K_{j-1} and K_j and its value is zero on $[0,a]\backslash(K_{j-1}\cup K_j)$. If n_* lies between y_j and y_{j+1}, then Φ_{n_*} is a real quadratic function on K_j and its value is zero on $[0,a]\backslash K_j$. We have $\Phi_{n_*}(y)=\phi_n(y)$, where $y\in K$, $n_*=L_1(K,n)$. Let u_{n_*}, v_{n_*} be the values of u_h, v_h at the nodes n_*, $n_*\in J_*$. Retaining our convention about $n_*=L_1(K,n)$, we do not write in the sequel the conditions $n\neq 1$ for $K=K_0$ and $n\neq 3$ for $K=K_N$. We have

$$u_h(y)=\sum_{n_*\in J_*}u_{n_*}\Phi_{n_*}(y)=\sum_{K\in\ \mathcal{T}_h, y\in K}\ \sum_{n\in\ J}u_{n_*}\phi_n(y)$$

and a similar expression for $v_h(y)$.

In order to obtain p_h, we use a basis of real functions of M_h. Let $I=I_K=\{1,2\}$ be the local numeration for the nodes of K, where $1,2$ correspond to y_j, y_{j+1} respectively. Let $\{\psi_m, m\in I\}$ be the local affine basis of functions on K corresponding to the local nodes. Let $I_*=\{0,1,\ldots,N,N+1\}$ be the global numeration for the nodes of $[0,a]$ and let L_2 be a matrix whose elements are the elements of I_*. Its rows are indexed by the elements $K\in\ \mathcal{T}_h$ and its columns, by the local numeration $m\in\ I$. Write $m_*=L_2(K,m)$ or, simply, m_* for the element m_* of L_2 which depends on K and m. Let $\{\Psi_{m_*}, m_*\in I_*\}$ be a basis of functions of M_h. If m_* corresponds to y_j, then Ψ_{m_*} is a real affine function on K_{j-1} and K_j and its value is zero on $[0,a]\backslash(K_{j-1}\cup K_j)$. We have $\Psi_{m_*}(y)=\Psi_m(y)$, where $y\in K$, $m_*=L_2(K,m)$. Let p_{m_*} be the values of p_h at the nodes m_*, $m_*\in I_*$. We have

$$p_h(y)=\sum_{m_*\in I_*}p_{m_*}\Psi_{m_*}(y)=\sum_{K\in\ \mathcal{T}_h, y\in K}\ \sum_{m\in\ I}p_{m_*}\psi_m(y).$$

Problem (8) - (10) becomes the following algebraic eigenvalue problem in $(c_h,\, u_1, v_1,\, \ldots,\, u_{2N+1}, v_{2N+1},\, p_0,\, \ldots,\, p_{N+1})\in\mathbb{C}^{1+2(2N+1)+N+2}$

$$\begin{aligned}&\sum_{K\in\ \mathcal{T}_h}\ \sum_{n\in\ J}u_{n_*}[-\alpha Re^{-1}i\int\limits_K\phi_n\phi_k dz-(\alpha Re)^{-1}i\int\limits_K\phi'_n\phi'_k dz+\\ &+\int\limits_K U\phi_n\phi_k dz]+\sum_{K\in\ \mathcal{T}_h}\ \sum_{n\in\ J}v_{n_*}[-\alpha^{-1}i\int\limits_K U'\phi_n\phi_k dz]+\\ &+\sum_{K\in\ \mathcal{T}_h}\ \sum_{m\in\ I}p_{m_*}\int\limits_K\psi_m\phi_k dz=c_h\cdot\{\sum_{K\in\ \mathcal{T}_h}\ \sum_{n\in\ J}u_{n_*}\int\limits_K\phi_n\phi_k dz\}\end{aligned}\tag{11}$$

$$\begin{aligned}
&\sum_{K\in\ \mathcal{T}_h}\sum_{n\in\ J} v_{n_*}[-\alpha Re^{-1} i \int_K \phi_n\phi_k dz - (\alpha Re)^{-1} i \int_K \phi'_n\phi'_k dz \\
&\quad + \int_K U\phi_n\phi_k dz] + \sum_{K\in\ \mathcal{T}_h}\sum_{m\in\ I} p_{m_*}[\alpha^{-1} i \int_K \psi_m\phi'_k dz] \\
&\quad = c_h\cdot\{\sum_{K\in\ \mathcal{T}_h}\sum_{n\in\ J} v_{n_*}\int_K \phi_n\phi_k dz\}
\end{aligned} \tag{12}$$

$$\begin{aligned}
&\sum_{K\in\ \mathcal{T}_h}\sum_{m\in\ I} p_{m_*}[-\alpha^2 \int_K \psi_m\psi_\ell dz - \int_K \psi'_m\psi'_\ell dz] \\
&\quad = -\sum_{K=K_N;\ n\in\ J_{K_N};n\neq 3} v_{n_*} Re^{-1}\Phi''_{n_*}(a)\Psi_{N+1}(a) \\
&\quad + \sum_{K=K_0;\ n\in\ J_{K_0};n\neq 1} v_{n_*} Re^{-1}\Phi''_{n_*}(0)\Psi_1(0) \\
&\quad + \sum_{K\in\ \mathcal{T}_h}\sum_{n\in\ J} v_{n_*}(-2\alpha i\int_K U'\phi_n\psi_\ell dz),
\end{aligned} \tag{13}$$

for all $k\in J$, $\ell\in I$, for all $K\in\ \mathcal{T}_h$, $k\neq 1$ when $K=K_0$, $k\neq 3$ when $K=K_N$.

The eigenvalue problem in $c_h\in\mathbb{C}$, $A_h = (\ u_1, v_1,\ \dots,\ u_{2N+1}, v_{2N+1})\in\mathbb{C}^{2(2N+1)}$, $B_h = (\ p_0,\ p_1,\ \dots,\ p_{N+1})\in\mathbb{C}^{N+2}$ represented by relations (11) - (13) can be written in the following matrix form

$$K_hA_h + L_hB_h = c_hS_hA_h, \quad G_hB_h = H_hA_h, \tag{14}$$

where $K_h, S_h\in\mathbb{C}^{2(2N+1)\times 2(2N+1)}$, $L_h\in\mathbb{C}^{2(2N+1)\times(N+2)}$, $G_h\in\mathbb{C}^{(N+2)\times(N+2)}$, $H_h\in\mathbb{C}^{(N+2)\times 2(2N+1)}$.

Matrix G_h is positive definite and symmetric. So problem (14) becomes

$$(K_h + L_hG_h^{-1}H_h)A_h = c_hS_hA_h, \quad B_h = G_h^{-1}H_hA_h, \tag{15}$$

The eigenvalue problem given by the first equation of (15) can be solved by using the QZ method or, after multiplication by S_h^{-1} at the left, by using the QR or LR method.

4 Possible applications to concrete fluid flows

Once (15) solved, several linear hydrodynamic stability characteristics can be determined numerically. Keeping α and Re fixed, (15) yields approximations of c and of amplitude distributions $u(y)$, $v(y)$ and $p(y)$. Repeating this operation with various values of α and Re, we can identify the pairs (Re, α) where the approximate value $c_i = 0$. Thus, we can construct the neutral curve. We also can determine the curves $c_i(Re, \alpha) = constant$ of constant amplification factor and the wave speed $c_r(Re, \alpha)$, for (Re, α) belonging to the neutral curve.

In particular, problem (15) is the basis of a computer program for the case of Prandtl's boundary layer, which will be presented elsewhere.

References

[1] Georgescu, A., *Hydrodynamic stability theory*, Kluwer, Dordrecht, 1985.

[2] Doering, Ch.R., Gibbon, J.D., *Applied analysis of the Navier-Stokes equations*, Cambridge University Press, 1995.

[3] Tollmien, W., *ber die Entstehung der Turbulenz*, Nacht. Ges. Wiss. Gttingen, Math. Phys. Klasse, 1 (1929), 21-44.

[4] Girault, V., Raviart, P.-A., *Finite element methods for Navier-Stokes equations. Theory and algorithms*, Springer, Berlin, 1986.

[5] Cuvelier, C., Segal, A., van Steenhoven, A.A., *Finite element methods and Navier-Stokes equations*, Reidel, Amsterdam, 1986.

[6] Bichir, C.L., *Theoretical and numerical hydrodynamic stability*, Electus, Piteşti, 2002.